















CROSSWALK AND LIMIT LINE See Note 5

Caltrans



WORD MARKINGS			
ITEM	m ²	ITEM	m2
LANE	2.23	NO	1.30
P00L	2.14	BIKE	1.95
CAR	1.58	BUS	1.86
CLEAR	2.51	ONL Y	2.04
KEEP	2.23		
	ITEM LANE POOL CAR CLEAR	ITEM m2 LANE 2.23 POOL 2.14 CAR 1.58 CLEAR 2.51	ITEM m2 ITEM LANE 2.23 NO POOL 2.14 BIKE CAR 1.58 BUS CLEAR 2.51 ONLY

NOTES

- (I) If a message consists of more than one word, it should read "UP", i.e., the first word should be nearest the driver.
- (2) The space between words should be at least four times the height of the characters for low speed roads, but not more than ten times the height of the characters. The space may be reduced appropriately where there is limited space because of local conditions.
- (3) Minor variations in dimensions may be accepted by the Engineer.
- (4) Portions of a letter, number or symbol may be separated by connecting segments not to exceed 50 mm in width.
- (5) Crosswalks contiguous to school grounds are to be 300 mm yellow lines in place of 300 mm white shown.

STATE OF CALIFORNIA DEPARTMENT OF TRANSPORTATION

PAVEMENT MARKINGS WORDS AND CCROSSWALKS

NO SCALE

ALL DIMENSIONS ARE IN MILLIMETERS UNLESS OTHERWISE SHOWN



1999

7